

2017



TRUCK AND BUS TYRE CATALOG

VERSION 1.0

YTH1



Suitable for various road conditions



YTH2



Suitable for high way and regional road conditions



Wear-resisting formula



Classic 3 grooves design
Designed for different complicated conditions



ALL POSITION
Recommended

Size	PR	SS	Standard Rim	LI	Tread Depth
7.50R16LT	12	K	6.00G	120/116	11.5
7.50R16LT	14	K	6.00G	122/118	11.5
8.25R16LT	14	K	6.50H	126/122	11.5
8.25R16LT	16	K	6.50H	128/124	11.5
8.25R20	14	K	6.5	136/134	12.5
8.25R20	16	K	6.5	139/137	12.5
9.00R20	14	K	7.0	141/139	13.5
9.00R20	16	K	7.0	144/142	13.5
10.00R20	16	K	7.5	146/143	14.5
10.00R20	18	K	7.5	149/146	14.5
11.00R20	16	K	8.0	150/147	16.5

Size	PR	SS	Standard Rim	LI	Tread Depth
11.00R20	18	K	8.0	152/149	16.5
12.00R20	18	K	8.5	154/151	16.5
12.00R20	20	K	8.5	156/153	16.5
12.00R24	18	K	8.5	158/155	15.0
12.00R24	20	K	8.5	160/157	15.0
11R22.5	14	K	8.25	144/142	16.0
11R22.5	16	K	8.25	146/143	16.0
315/80R22.5	18	L	9.00	154/151	16.5
315/80R22.5	20	L	9.00	156/150	16.5
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5

Size	PR	SS	Standard Rim	LI	Tread Depth
9.00R20	14	K	7.0	141/139	15.0
9.00R20	16	K	7.0	144/142	15.0
10.00R20	16	K	7.5	146/143	17.0
10.00R20	18	K	7.5	149/146	17.0
11.00R20	16	K	8.0	150/147	17.0
11.00R20	18	K	8.0	152/149	17.0
11R22.5	14	K	8.25	144/142	17.0
11R22.5	16	K	8.25	146/143	17.0
10R22.5	14	L	7.50	141/139	15.0
10R22.5	16	L	7.50	144/142	15.0



Wear-resisting formula



Continuous tire shoulder prevents irregular wear
4 grooves design provides good drainage performance



ALL POSITION
Recommended

YTH3



Suitable for normal road condition and middle distance



Optimized bead and belt structure make a strong tire body

Super wide section provides driving stability and long mileage

The combination of transverse and longitudinal pattern makes a good balance of traction and handling

ALL POSITION
Recommended



Size	PR	SS	Standard Rim	LI	Tread Depth
9.00R20	14	K	7.0	141/139	15.0
9.00R20	16	K	7.0	144/142	15.0
10.00R20	16	K	7.5	146/143	16.0
10.00R20	18	K	7.5	149/146	16.0
11.00R20	16	K	8.0	150/147	16.5
11.00R20	18	K	8.0	152/149	16.5
12.00R20	18	K	8.5	154/151	16.5
12.00R20	20	K	8.5	156/153	16.5
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5
10R22.5	14	L	7.50	141/139	15.0
10R22.5	16	L	7.50	144/142	15.0

YTH4



Suitable for high way condition and long distance



Continuous tire shoulder prevents irregular wear

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage

ALL POSITION
Recommended



Size	PR	SS	Standard Rim	LI	Tread Depth
215/75R17.5	16	J	6.00	135/133	12.5
225/70R19.5	12	M	6.75	125/123	12.5
225/70R19.5	14	M	6.75	128/126	12.5
235/75R17.5	16	J	6.75	143/141	12.5
245/70R19.5	16	J	7.50	135/133	12.5
255/70R22.5	16	J	7.50	140/137	12.5
265/70R19.5	14	J	7.50	137/134	12.5
265/70R19.5	16	J	7.50	143/141	12.5
275/70R22.5	16	J	8.25	144/141	14.5
275/70R22.5	16	J	8.25	148/145	14.5
11R22.5	14	K	8.25	144/142	14.5
11R22.5	16	K	8.25	146/143	14.5
11R24.5	14	K	8.25	146/143	14.5
11R24.5	16	K	8.25	149/146	14.5
295/75R22.5	14	K	9.00	144/141	14.5
295/75R22.5	16	K	9.00	146/143	14.5
285/75R24.5	14	K	8.25	144/141	14.5
285/75R24.5	16	K	8.25	147/144	14.5

YTH6



Suitable for high way and regional road conditions



High mileage assured with super deep tread

Lateral blocks provide excellent traction power

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

DRIVE OR TRAILER

Recommended



Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	21.5
11R22.5	16	K	8.25	146/143	21.5
11R24.5	14	K	8.25	146/143	21.5
11R24.5	16	K	8.25	149/146	21.5
295/75R22.5	14	K	9.00	144/141	21.5
295/75R22.5	16	K	9.00	146/143	21.5
285/75R24.5	14	K	8.25	144/141	21.5
285/75R24.5	16	K	8.25	147/144	21.5

YTH7



Suitable for high way condition



Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5
295/80R22.5	16	L	9.00	150/147	14.5
295/80R22.5	18	L	9.00	152/149	14.5
13R22.5	16	K	9.75	152/149	14.5
315/80R22.5	18	L	9.00	154/151	14.5
315/80R22.5	20	L	9.00	156/150	14.5



Compact pattern design provides longer mileage

Continuous tire shoulder prevents irregular wear

4 straight grooves bring great steering performance

STEER OR TRAILER

Recommended



YTH6



Suitable for high way and regional road conditions



YTH7



Suitable for high way condition



High mileage assured with super deep tread

Lateral blocks provide excellent traction power

Special protrusions at the bottom of grooves avoid groove crack and clamping stones



DRIVE OR TRAILER

Recommended

Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	21.5
11R22.5	16	K	8.25	146/143	21.5
11R24.5	14	K	8.25	146/143	21.5
11R24.5	16	K	8.25	149/146	21.5
295/75R22.5	14	K	9.00	144/141	21.5
295/75R22.5	16	K	9.00	146/143	21.5
285/75R24.5	14	K	8.25	144/141	21.5
285/75R24.5	16	K	8.25	147/144	21.5

Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5
295/80R22.5	16	L	9.00	150/147	14.5
295/80R22.5	18	L	9.00	152/149	14.5
13R22.5	16	K	9.75	152/149	14.5
315/80R22.5	18	L	9.00	154/151	14.5
315/80R22.5	20	L	9.00	156/150	14.5



Compact pattern design provides longer mileage

Continuous tire shoulder prevents irregular wear

4 straight grooves bring great steering performance



STEER OR TRAILER

Recommended

YTH8



Suitable for high way and regional road conditions



Wear-resisting formula



High mileage assured with super deep tread

Lateral blocks provide excellent traction power

Size	PR	SS	Standard Rim	LI	Tread Depth
295/80R22.5	16	L	9.00	150/147	21.5
295/80R22.5	18	L	9.00	152/149	21.5
315/80R22.5	18	L	9.00	154/151	22.5
315/80R22.5	20	L	9.00	156/150	22.5
12R22.5	16	L	9.00	150/147	17.0
12R22.5	18	L	9.00	152/149	17.0
11R22.5	14	K	8.25	144/142	22.5
11R22.5	16	K	8.25	146/143	22.5
11.00R20	16	K	8.0	150/147	17.0
11.00R20	18	K	8.0	152/149	17.0



DRIVE
Recommended

YTH10



Suitable for high way condition



Continuous tire shoulder prevents irregular wear

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage

Size	PR	SS	Standard Rim	LI	Tread Depth
385/65R22.5	20	K	11.75	160	15.0



STEER OR TRAILER
Recommended

YTH12



Suitable for high way condition



Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	15.0
12R22.5	18	L	9.00	152/149	15.0



Continuous tire shoulder prevents irregular wear

Irregular sequence pattern pitch design reduces noise efficiently

Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage

STEER OR TRAILER

Recommended



YTH13



Suitable for high way condition



Size	PR	SS	Standard Rim	LI	Tread Depth
12R22.5	16	L	9.00	150/147	15.0
12R22.5	18	L	9.00	152/149	15.0



Continuous tire shoulder prevents irregular wear

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage

STEER OR TRAILER

Recommended



YTH15



Suitable for high way condition



Continuous tire shoulder prevents irregular wear

Irregular sequence pattern pitch design reduces noise efficiently

Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage

STEER OR TRAILER

Recommended



Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	14.5
11R22.5	16	K	8.25	146/143	14.5

YTH17



Suitable for mix road condition



Wear-resisting formula



High mileage assured with super deep tread

Ultra strong structure provides excellent high load capacity

Size	PR	SS	Standard Rim	LI	Tread Depth
10.00R20	16	K	7.5	146/143	20.0
10.00R20	18	K	7.5	149/146	20.0
11.00R20	16	K	8.0	150/147	20.0
11.00R20	18	K	8.0	152/149	20.0
12.00R20	18	K	8.5	154/151	20.0
12.00R20	20	K	8.5	156/153	20.0
12R22.5	16	M	9.00	150/147	18.0
12R22.5	18	L	9.00	152/149	18.0



DRIVE OR TRAILER

Recommended

YTH18



Suitable for high way and regional road conditions



Continuous tire shoulder prevents irregular wear

3 grooves design provides good drainage performance and driving stability

Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	16.5
11R22.5	16	K	8.25	146/143	16.5
12R22.5	16	L	9.00	150/147	16.5
12R22.5	18	L	9.00	152/149	16.5

ALL POSITION
Recommended



YTH19



Suitable for high way and regional road conditions



High mileage assured with super deep tread

Lateral blocks provide excellent traction power

Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	14	K	8.25	144/142	18.5
11R22.5	16	K	8.25	146/143	18.5
12R22.5	16	K	9.00	150/147	19.5
12R22.5	18	K	9.00	152/149	19.5

DRIVE OR TRAILER
Recommended



YT102



Suitable for high way condition



Wear-resisting formula



Continuous tire shoulder prevents irregular wear

Irregular sequence pattern pitch design reduces noise efficiently

Size	PR	SS	Standard Rim	LI	Tread Depth
7.00R16LT	10	L	5.50F	111/107	11.5
7.00R16LT	12	L	5.50F	115/110	11.5
7.50R20	12	L	6.0	128/126	12.5
7.50R20	14	L	6.0	130/128	12.5

YT902



Suitable for on-off road conditions



Anti-puncture formula



Ultra strong structure provides excellent high load capacity

Football pattern design and deep groove bring excellent traction and braking ability

Size	PR	SS	Standard Rim	LI	Tread Depth
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	20.0
12.00R20	20	K	8.5	156/153	20.0

ALL POSITION

Recommended



DRIVE OR TRAILER

Recommended



YT903



Suitable for on-off road conditions



Anti-puncture formula



Lateral blocks provide excellent traction power

Arc-shape groove design provides good drainage performance

Size	PR	SS	Standard Rim	LI	Tread Depth
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	19.5
12.00R20	20	K	8.5	156/153	19.5



DRIVE OR TRAILER
Recommended

YT906



Suitable for off road conditions



Anti-puncture formula



Big strong block design improves the off-road ability

Unique pattern design brings excellent driving and braking ability

Size	PR	SS	Standard Rim	LI	Tread Depth
7.50R16LT	12	E	6.00G	120/116	18.5
7.50R16LT	14	D	6.00G	122/118	18.5
8.25R16LT	14	E	6.50H	126/122	18.5
8.25R16LT	16	D	6.50H	128/124	18.5
8.25R20	14	E	6.5	136/134	18.5
8.25R20	16	D	6.5	139/137	18.5
10.00R20	16	E	7.5	146/143	25.2
10.00R20	18	D	7.5	149/146	25.2
11.00R20	16	E	8.0	150/147	25.2
11.00R20	18	D	8.0	152/149	25.2
12.00R20	18	E	8.5	154/151	25.2
12.00R20	20	D	8.5	156/153	25.2



DRIVE OR TRAILER
Recommended

YT906+



Suitable for off road conditions



Anti-puncture formula



Lateral blocks provide excellent traction power

Big strong block design improves the off-road ability

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

DRIVE OR TRAILER

Recommended



YT907



Suitable for on-off road condition and short distance



Anti-puncture formula



Lateral blocks provide excellent traction power

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

DRIVE OR TRAILER

Recommended



Size	PR	SS	Standard Rim	LI	Tread Depth
12.00R20	18	E	8.5	154/151	23.2
12.00R20	20	D	8.5	156/153	23.2

Size	PR	SS	Standard Rim	LI	Tread Depth
7.50R16LT	12	K	6.00G	120/116	14.5
7.50R16LT	14	K	6.00G	122/118	14.5
8.25R16LT	14	K	6.50H	126/122	14.5
8.25R16LT	16	K	6.50H	128/124	14.5
8.25R20	14	K	6.5	136/134	14.5
8.25R20	16	K	6.5	139/137	14.5
9.00R20	14	K	7.0	141/139	16.5
9.00R20	16	K	7.0	144/142	16.5
10.00R20	16	K	7.5	146/143	17.5
10.00R20	18	K	7.5	149/146	17.5
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	18.5
12.00R20	20	K	8.5	156/153	18.5

YT908



Suitable for mix road condition



Anti-crack formula



Lateral blocks provide excellent traction and braking power

Ultra strong structure provides excellent high load capacity

Size	PR	SS	Standard Rim	LI	Tread Depth
9.00R20	14	K	7.0	141/139	17.5
9.00R20	16	K	7.0	144/142	17.5
10.00R20	16	K	7.5	146/143	18.5
10.00R20	18	K	7.5	149/146	18.5
11.00R20	16	K	8.0	150/147	19.5
11.00R20	18	K	8.0	152/149	19.5
12.00R20	18	K	8.5	154/151	19.5
12.00R20	20	K	8.5	156/153	19.5

Drive

Recommended



YT919



Suitable for off road conditions



Anti-puncture formula



Lateral blocks provide excellent traction power

Big strong block design improves the off-road ability

Special protrusions at the bottom of grooves avoid groove crack and clamping stones

Size	PR	SS	Standard Rim	LI	Tread Depth
12.00R20	18	F	8.5	154/151	23.2
12.00R20	20	F	8.5	156/153	23.2
11.00R20	16	F	8.0	150/147	23.2
11.00R20	18	F	8.0	152/149	23.2
9.00R20	14	F	7.0	141/139	19.0
9.00R20	16	F	7.0	144/142	19.0

DRIVE

Recommended

