

Recommended Application

TBR & LTR

STEERING
Page:8-10

DRIVING
Page:11-16

ALL POSITION
Page:17-21

WIDE SINGLE TRAILER
Page:21-22



Recommended Application

TBR & LTR

SPECIAL
Page:22-24

USA SIZES
Page:24-25



TBR AVAILABLE SIZES AND TREAD PATTERNS

Size	Pattern	STEERING Page:8-10					DRIVING Page:11-16					
		GT298	GT298+	GT298++	YB288	GT128	GT267	GT296	GT296+	GT299	YB228	YB118
215/75R17.5						●						●
235/75R17.5						●						●
6.50R16LT											●	●
7.00R16LT											●	●
7.50R16LT											●	●
8.25R16LT											●	●
8.25R20												●
9.00R20											●	
10.00R20											●	
11.00R20											●	
12.00R20											●	
12.00R24											●	
11R22.5		●		●				●		●		
12R22.5		●	●	●		●		●		●		
13R22.5		●										
295/80R22.5		●		●					●	●		
315/80R22.5		●		●				●	●	●		
385/65R22.5												
425/65R22.5												

TBR AVAILABLE SIZES AND TREAD PATTERNS

Size	Pattern	DRIVING Page:11-16						ALL POSITION Page: 17-21						WIDE SINGLE TRAILER Page:21-22			SPECIAL Page:22-24				USA SIZES Page:24-25						
		YB258	YB900	YB866	YB398	GT918	GT286	GT277	YB/GT268	YB218	YB318+	YB368	GT288+	GT198	GT269	GT266	YB366	GT295	GT395	GT359	YB/GT328	YB338	YB388	YB988	AD818A	AD868	AD856
6.50R16LT								•																			
7.00R16LT								•														•					
7.50R16LT								•														•					
8.25R16LT								•			•											•					
8.25R20								•														•					
9.00R20			•					•			•											•					
10.00R20	•	•	•					•														•		•			
11.00R20	•			•				•		•	•											•	•	•	•		
12.00R20	•			•				•		•	•					•						•	•	•	•		
12.00R24								•				•															
11R22.5								•														•			•	•	
12R22.5					•	•		•	•					•	•											•	
13R22.5								•														•					
295/80R22.5																						•					
315/80R22.5							•	•																			
385/65R22.5																	•	•									
425/65R22.5																					•						
275/70R22.5													•														
295/75R22.5																									•	•	•
285/75R24.5																									•	•	
11R24.5																									•	•	•



GT298



- Easy handling
- Tough belt construction reduces heating and irregular wear
- Special tread compound provides longer mileage and minimizes tread injuries
- Quiet and smooth riding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11R22.5	TL	16	146/143	M	1054	279	15.0	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	15.0	9.00	3550	3250	930
13R22.5	TL	18	154/151	L	1124	320	15.0	9.75	3750	3450	830
295/80R22.5	TL	18	152/149	L	1044	298	15.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	15.0	9.00	4125	3750	900



GT298++



- Adopted "Plus+" concept
- Added more mileage
- widen tread width and revised land/sea ratio
- Given more stability
- widen shoulder and center rib given more road holding
- 11R22.5, extra mileage

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11R22.5	TL	16	146/143	M	1054	279	15.0	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	16.5	9.00	3550	3250	930
295/80R22.5	TL	18	152/149	L	1044	298	15.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	15.0	9.00	4125	3750	900



GT298+



- Easy handling
- Tough belt construction reduces heating and irregular wear
- Special tread compound provides longer mileage and minimizes tread injuries
- Quiet and smooth riding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930



YB288



- Three main grooves and two block type ribs on the tread center provide good traction on wet and dry road conditions
- Special anti-cut tread compound provides high resistance for cut and chipping
- Easy handling
- Tough belt construction for smooth tread wear

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
7.00R16LT	TT	14	118/114	L	775	200	12.0	5.50F	1320	1180	770
10.00R20	TT	18	149/146	K	1054	278	16.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	16.5	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	16.5	8.5	4000	3650	900



GT128



- Easy handling
- Tough belt construction reduces heating and irregular wear
- Special tread compound provides longer mileage and minimizes tread injuries
- Quiet and smooth riding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
215/75R17.5	TL	16	127/124	L	767	211	13.5	6.00	1750	1600	830
235/75R17.5	TL	16	132/129	J	797	233	13.5	6.75	2000	1850	830
225/70R19.5	TL	14	128/126	L	811	226	14.0	6.75	1800	1700	760
245/70R19.5	TL	16	135/133	L	839	248	14.0	7.50	2180	2060	830



GT296



- Adopted convex-shaped blocks for higher gripping power on both wet and dry road conditions
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for minimizing tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11R22.5	TL	16	146/143	L	1054	279	18.0	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	20.5	9.00	3550	3250	930
315/80R22.5	TL	20	157/154	L	1076	312	20.5	9.00	4125	3750	900



GT267



- Easy handling
- Tough belt construction reduces heating and irregular wear
- Special tread compound provides longer mileage and minimizes tread injuries
- Quiet and smooth riding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	16.5	9.00	3550	3250	930



GT296+



- Adopted "plus+" concept
- Added more mileage
 - Widen tread width
 - Increased road contact area
- Increased gripping power

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
295/80R22.5	TL	18	152/149	L	1044	298	18.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	18.0	9.00	4125	3750	900



GT299



- Opened shoulder and blocks on the tread center provide high traction power on both wet and dry road conditions
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for minimizing tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11R22.5	TL	16	146/143	L	1054	279	18.0	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	18.0	9.00	3550	3250	930
295/80R22.5	TL	18	152/149	L	1044	298	20.0	9.00	3550	3250	900
315/80R22.5	TL	20	157/154	L	1076	312	20.0	9.00	4125	3750	900



YB228



- Strong shoulder lugs provides excellent gripping power on muddy road conditions
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for high resistance against tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
6.50R16LT	TT	10	107/102	L	750	185	12.5	5.50F	975	850	560
7.00R16LT	TT	14	118/114	L	775	200	14.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	805	215	14.0	6.00G	1500	1320	770
8.25R16LT	TT	16	128/124	K	855	235	16.5	6.50H	1800	1600	770
9.00R20	TT	16	144/142	K	1019	259	17.5	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	18.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	21.5	8.0	3550	3250	930
12.00R20	TT	18	154/151	J	1125	315	22.0	8.5	3750	3450	830
12.00R24	TT	20	160/157	K	1226	315	22.0	8.5	4500	4125	900



YB258



- Block tread pattern provides excellent gripping power on both wet and dry road conditions
- Tough belt construction for smooth wear and longer mileage
- Special tread compound for high resistance against tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1054	278	16.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	17.5	8.0	3550	3250	930
12.00R20	TT	18	154/151	J	1125	315	17.5	8.5	3750	3450	830



YB900



- Special pattern design provides good traction and driving capacity
- Special rib and lug mixed pattern for smooth tread wear
- High safety and re-capping capacity

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
9.00R20	TT	16	144/142	K	1019	259	18.0	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	18.5	7.5	3250	3000	930



YB866



- Special pattern design provides good traction and driving capacity
- Tough belt for smooth tread wear and longer mileage
- Special compound for high resistance against tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1054	278	18.5	7.5	3250	3000	930



YB398



- Block tread design provide strong traction and breaking power
- Tough belt construction for smooth wear and longer mileage
- Reinforced bead and body to ensure durability

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11.00R20	TT	18	152/149	K	1089	293	20.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1126	315	21.0	8.5	4000	3650	900



YB118



- Lug groove provide more traction
- Special tread design for mixed road condition
- Reinforced bead and body to ensure durability

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
215/75R17.5	TL	16	127/124	L	767	211	13.5	6.00	1750	1600	830
235/75R17.5	TL	16	132/129	J	797	233	13.5	6.75	2000	1850	830
6.50R16LT	TT	12	110/105	L	754	185	14.0	5.50F	1060	925	670
7.00R16LT	TT	14	118/114	L	775	200	15.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	L	810	215	15.5	6.00G	1500	1320	770
8.25R16LT	TT	16	128/124	L	853	235	15.5	6.50H	1800	1600	770
8.25R20	TT	16	139/137	K	970	236	16.5	6.5	2430	2300	930



GT918



- Special pattern design provides good traction and driving capacity
- Tough belt for smooth tread wear and longer mileage
- Special compound for high resistance against tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	18.0	9.00	3550	3250	930



GT286



- Special pattern design provides good traction and driving capacity
- Tough belt for smooth tread wear and longer mileage
- Special compound for high resistance against tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1096	300	21.0	9.00	3550	3250	930



YB268 GT268



- Shoulder lugs for more traction and center rids are for stable handling
- Tough belt for smooth wear and longer mileage
- Special tread compound for high resistance tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
6.50R16LT	TT	10	107/102	L	750	185	10.5	5.50F	975	850	560
7.00R16LT	TT	14	118/114	L	775	200	12.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	K	805	215	13.0	6.00G	1500	1320	770
8.25R16LT	TT	16	128/124	K	855	235	14.5	6.50H	1800	1600	770
8.25R20	TT	16	139/137	K	974	236	15.0	6.5	2430	2300	930
9.00R20	TT	16	144/142	K	1019	259	15.5	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1054	278	16.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1085	293	17.0	8.0	3550	3250	930
12.00R20	TT	18	154/151	J	1125	315	17.5	8.5	3750	3450	830
12.00R24	TT	20	160/157	K	1226	315	17.5	8.5	4500	4125	900
11R22.5	TL	16	146/143	M	1054	279	17.5	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930
315/80R22.5	TL	20	157/154	L	1076	312	18.0	9.00	4125	3750	900



GT277



- Block tread design provide strong traction and breaking power
- Tough belt construction for smooth wear and longer mileage
- Reinforced bead and body to ensure durability

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
315/80R22.5	TL	20	157/154	L	1076	312	22.0	9.00	4125	3750	900



GT218



- Wide tread design to extend tire service life
- Low rolling resistance and excellent heat dispersion performance
- Wide shoulder provide excellent road holding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930

YB318+



- Adopted "plus+" concept
- Zigzag block provide excellent traction and braking power
- Special compound and waterproof and anti-puncturing construction
- Reinforced bead and body construction improve durability
- Tough tread blocks for high traction on the muddy road

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11.00R20	TT	18	152/149	K	1085	293	20.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	20.0	8.5	4000	3650	900

YB368



- Big block provide strong traction and braking power
- Open groove and bottom design given very good self-cleaning performance.
- Open shoulder reduce heat
- Reinforced bead and body to ensure durability

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
8.25R16LT	TT	16	128/124	K	855	235	15.5	6.50H	1800	1600	770
9.00R20	TT	16	144/142	K	1019	259	18.0	7.0	2800	2650	900
11.00R20	TT	18	152/149	K	1085	293	19.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1125	315	21.5	8.5	4000	3650	900

GT288+



- Wider tread and deeper tread for long mileage
- Special tread compound for cut protection and reducing heating
- Tough belt construction for smooth tread wear

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12.00R24	TT	20	160/157	K	1226	315	16.0	8.5	4500	4125	900

GT198



- CBS: City Bus Service
- Special tread design for city bus
- Cool-Wind decoration on the sidewall
- Special tread compound for cut protection and reducing heating
- Tough belt construction for smooth tread wear

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
275/70R22.5	TL	16	144/141	J	964	276	22.5	8.25	2800	2575	830

GT269



- Shoulder lugs for more traction and center rids are for stable handling
- Tough belt for smooth wear and longer mileage
- Special tread compound for high resistance tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.5	9.00	3550	3250	930

GT266



- Wide tread design to extend tire service life
- Low rolling resistance and excellent heat dispersion performance
- Wide shoulder provide excellent road holding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12R22.5	TL	18	152/149	L	1085	300	17.0	9.00	3550	3250	930

YB366



- Wide tread design to extend tire service life
- Low rolling resistance and excellent heat dispersion performance
- Wide shoulder provide excellent road holding

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
12.00R20	TT	20	156/153	J	1125	315	18.0	8.50	4000	3650	900

GT295



- Added more gripping power
- Tough belt construction for smooth tread wear
- Special compound for more mileage and cut protection

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
385/65R22.5	TL	20	160	K	1072	389	16.0	11.75	4500	900	

GT395



- Added more gripping power
- Tough belt construction for smooth tread wear
- Special compound for more mileage and cut protection

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
385/65R22.5	TL	20	160	K	1066	389	16.0	11.75	4500	900	



GT359



- For Wide—Single Trailer
- Tough belt construction for smooth tread wear
- Special compound for more mileage and cut protection

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
425/65R22.5	TL	20	165	K	1120	424	18.5	13.0	5150		830



YB338



- Special tread design for high traction on wet and muddy road
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for high resistant tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11.00R20	TT	18	152/149	F	1096	293	22.0	8.0	3550	3250	900
12.00R20	TT	20	156/153	J	1136	315	16.5	8.5	4000	3650	900



YB328 GT328



- Special tread design for high traction on wet and muddy road
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for high resistant tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
10.00R20	TT	18	149/146	K	1065	278	20.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1096	293	21.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1136	315	21.5	8.5	4000	3650	900
11R22.5	TL	16	146/143	E	1065	279	19.5	8.25	3000	2725	830
13R22.5	TL	18	154/151	L	1136	320	21.5	9.75	3750	3450	830
295/80R22.5	TL	18	152/149	L	1050	298	22.0	9.00	3550	3250	900



YB388



- Wide tread and revised land/sea ratio given more mileage
- Open groove on the shoulder given good heat dispersion performance
- Special compound provide excellent service life and cut resistance

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
7.00R16LT	TT	14	118/114	L	785	200	20.0	5.50F	1320	1180	770
7.50R16LT	TT	14	122/118	L	819	215	20.0	6.00G	1500	1320	770
8.25R16LT	TT	16	128/124	L	864	235	21.0	6.50H	1800	1600	770
8.25R20	TT	16	139/137	K	986	236	21.0	6.5	2430	2300	930
9.00R20	TT	16	144/142	K	1030	259	22.0	7.0	2800	2650	900
10.00R20	TT	18	149/146	K	1065	278	23.5	7.5	3250	3000	930
11.00R20	TT	18	152/149	K	1096	293	23.5	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1136	315	24.0	8.5	4000	3650	900



YB988



- Wide tread and revised land/sea ratio given more mileage
- Open groove on the shoulder given good heat dispersion performance
- Special compound provide excellent service life and cut resistance

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
11.00R20	TT	18	152/149	J	1096	293	24.0	8.0	3550	3250	930
12.00R20	TT	20	156/153	J	1133	315	24.5	8.5	4000	3650	900



AD868



- Opened shoulder and blocks on the tread center provide high traction power on both wet and dry road conditions
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for minimizing tread cut

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
295/75R22.5	TL	16	146/143	M	1022	298	21.0	9.00	3000	2725	830
285/75R24.5	TL	16	147/144	M	1057	283	21.0	8.25	3075	2800	830
11R22.5	TL	16	146/143	M	1058	279	21.0	8.25	3000	2725	830
12R22.5	TL	18	152/149	L	1092	300	21.0	9.00	3550	3250	930
11R24.5	TL	16	149/146	M	1092	279	21.0	8.25	3250	3000	830



AD818A



- **DECOUPLING**
- Wide tread and revised land/sea ratio given more mileage
- Special compound provide excellent service life and cut resistance

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
295/75R22.5	TL	16	146/143	M	1012	298	16.0	9.00	3000	2725	830
285/75R24.5	TL	16	147/144	M	1047	283	16.0	8.25	3075	2800	830
11R24.5	TL	16	149/146	M	1099	279	16.0	8.25	3250	3000	830



AD856



- Wide tread and revised land/sea ratio given more mileage
- Special compound provide excellent service life and cut resistance

Size	Type	PR	Load Index	Speed Symbol	O.D (mm)	S.W (mm)	NSD (mm)	Rim (mm)	Max. Load (kg)		Max. Pressure (kPa)
									Single	Dual	
295/75R22.5	TL	16	146/143	M	999	298	10.5	9.00	3000	2725	830
11R22.5	TL	16	146/143	M	1039	279	11.0	8.25	3000	2725	830
11R24.5	TL	16	149/146	M	1087	279	10.5	8.25	3250	3000	830

Product Classification

TBB<B Page:20-23		OTR&ID Page:24-31			AG Page:32-34

XYB158



- Superior pattern design for powerful gripping and lower rolling resistance
- Special pattern for effective resistance to irregular wearing

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
8.25-16	TT	16	6.50H	855	235	12.0	1800	1600	730	730
7.00-20	TT	14	5.5	904	200	11.5	1750	1550	840	770
7.50-20	TT	14	6.0	935	215	11.5	1900	1700	810	740

XYB168



- Excellent pattern design,enhance the rigidity,effective the carcass construction,improve the durability
- Intensify the carcass construction,improve the durability
- Optimum grip and traction

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
6.50-16	TT	12	5.50F	750	185	9.0	1060	925	630	630
7.00-16	TT	14	5.50F	775	200	11.0	1320	1180	730	730
7.50-16	TT	14	6.00G	805	215	11.0	1500	1320	730	730
7.50-20	TT	14	6.00	935	215	13.0	1900	1700	810	740
8.25-16	TT	16	6.50H	855	235	12.0	1800	1600	730	730
8.25-20	TT	14	6.5	974	236	14.0	2240	1950	810	740
9.00-20	TT	14	7.0	1018	259	16.0	2575	2300	770	700
9.00-20	TT	16	7.0	1018	259	16.0	2900	2500	880	810
10.00-20	TT	16	7.5	1055	278	16.0	3000	2650	810	740
10.00-20	TT	18	7.5	1055	278	16.0	3350	2900	910	840
11.00-20	TT	18	8.0	1085	293	17.5	3650	3150	910	840
12.00-20	TT	18	8.5	1125	315	18.0	3750	3350	810	740

XYB166



- Superior pattern design for powerful gripping and lower rolling resistance
- Special pattern for effective resistance to irregular wearing

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
6.50-16	TT	10	5.50F	750	185	8.5	975	875	530	530
7.00-16	TT	14	5.50F	775	200	10.0	1320	1180	730	730
7.50-16	TT	14	6.00G	805	215	11.5	1500	1320	730	730

XYB169



- Superior pattern design for high resistance to tread wear
- Tough carcass construction for excellent over-loading and longer mileage
- Good gripping power and traction capacity

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load (kg)	Max.Pressure (kPa)
4.00-14	TT	8	3.00D	590	110	8.5	405	455
4.50-14	TT	8	3.00D	630	122	7.0	450	420
4.50-16	TT	6	3.00D	655	122	7.0	615	360
5.00-16	TT	8	4.00E	655	130	9.0	550	420
5.50-16	TT	10	4.00E	685	150	8.0	800	500
5.50-13	TT	8	4.00B	620	160	8.5	560	420
6.00-13	TT	8	4.50B	655	170	10.0	650	420
6.00-14	TT	10	4 1/2 J	680	170	10.0	800	530
6.00-16	TT	10	4.50E	730	170	8.5	850	530
6.50-14	TT	10	4 1/2 J	705	180	9.0	900	530

TBB<B

XYB198



- Superior pattern design for powerful gripping and lower rolling resistance
- Special pattern for effective resistance to irregular wearing

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
8.25-20	TT	14	6.5	974	236	12.0	2240	1950	810	740
9.00-20	TT	16	7.0	1018	259	14.0	2900	2500	880	810
10.00-20	TT	18	7.5	1055	278	14.0	3350	2900	910	840

YB310



- Strength nylon construction, excellent loading capacity Suitable for mining area & grinding condition
- Deepen pattern takes longer tread life
- Special formulation, effective resistance to irregular wearing & tearing solid carcass takes good over-loading performance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
6.50-16	TT	12	5.50F	761	185	16.0	1060	925	630	630
7.00-16	TT	14	5.50F	785	200	16.0	1320	1180	730	730
7.50-16	TT	14	6.00G	816	215	17.0	1500	1320	730	730
8.25-16	TT	16	6.50H	867	235	20.0	1800	1600	730	730
9.00-16	TT	16	6.50H	902	255	20.0	2120	1850	730	730
10.00-20	TT	18	7.5	1073	278	30.0	3350	2900	910	840
11.00-20	TT	18	8.0	1105	293	31.0	3650	3150	910	840
12.00-20	TT	18	8.5	1145	315	32.0	3750	3350	810	740

30

YB316



- Strength nylon construction, excellent loading capacity
- Suitable for mining area & grinding condition
- Deepen pattern takes longer tread life
- Special formulation, effective resistance to irregular wearing & tearing solid carcass takes good over-loading performance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
8.25-16	TT	18	6.50H	867	235	20.0	1800	1600	730	730
9.00-16	TT	18	6.50H	890	255	20.0	2120	1850	730	730

YB317



- Strength nylon construction, excellent loading capacity
- Suitable for mining area & grinding condition
- Deepen pattern takes longer tread life
- Special formulation, effective resistance to irregular wearing & tearing solid carcass takes good over-loading performance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
8.25-16	TT	18	6.50H	867	235	20.0	1800	1600	730	730
9.00-16	TT	18	6.50H	890	255	20.0	2120	1850	730	730

TBB & LTB

YB916



- Advanced strength carcass, enhances loading capacity
- Special block pattern, excellent traction and holding, provides delivers stability on mine, coal and dirt road
- Special rubber formulation, effective resistance to irregular wear, prevents from cutting & tearing

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
13.00-25	TT	32	10.00/1.5	1300	350	26.0	6000	3000	450	750
14.00-25	TT	32	10.00/1.5	1370	375	27.0	11000	6050	1000	725

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
13.00-20	TT	18	9.0	1200	340	21.0	4250	3750	770	700

YB919



- Special tread compound reduces heating, enhances durability
- Special block and lug pattern design, provides delivers stability effectively, resistance to cutting & tearing
- Adopts the strength cord construction & big figure frame, provides heavy loading.

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
12.00-24	TT	20	8.5	1290	320	39.0	3660	3485	700	700

32

YB917



- Advanced strength carcass, enhances loading capacity
- Special block pattern, excellent traction and holding, provides delivers stability on mine, coal and dirt road
- Special rubber formulation, effective resistance to irregular wear, prevents from cutting & tearing

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
14.00-24	TT	32	10.0	1370	375	28.0	10500	6050	1000	725

YB816



- Non-directional pattern and strength carcass structure makes exceptional traction and operation performance
- Resistance to cutting and treadwear, low heating

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
16/70-20	TT	14	13.0	1075	410	23.0	5150	2900	450	350
17.5-25	TT	12	14.00/1.5	1350	445	24.0	6150	3650	350	225
17.5-25	TT	16	14.00/1.5	1350	445	24.0	7300	4250	475	300
20.5-25	TT	20	17.00/2.0	1490	520	32.0	9500	6000	450	325
23.5-25	TT	20	19.50/2.5	1615	595	35.0	10900	7300	375	300
29.5-25	TT	28	25.00/3.5	1875	750	38.0	17500	11500	425	325
29.5-29	TL	34	25.00/3.5	1975	750	38.0	21200	14000	525	400

OTR & ID

33

YB818



- Non-directional pattern and strength carcass structure makes exceptional traction and operation performance
- Aggressive product formula makes sure excellent resistance to high heat

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
18.00-33	TL	40	13.00/2.5	1875	500	54.0	19500	11400	930	700

YB838



- Low heat generating for high speed
- Deep traction pattern for improved traction performance
- Excellent resistance to tearing and cutting, low tread wear and stable handling performance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
17.5-25	TT	12	14.00/1.5	1350	445	24.0	6150	3650	350	225
17.5-25	TT	16	14.00/1.5	1350	445	24.0	7300	4250	475	300

YB888



- Deep and wide tread design, strong resistance to cutting, tearing and treadwear
- Special shoulder makes good self-cleaning performance
- Aggressive formulation makes temperature resistance
- Strength and overstriking nylon cord provides extra loading capacity and attack resistance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
21.00-35	TL	40	15.00/3.0	2050	570	54.0	24300	14000	825	625
24.00-35	TL	48	17.00/3.5	2175	655	57.0	31500	18500	825	650
27.00-49	TL	48	19.50/4.0	2700	735	63.5	43750	25000	775	575
33.00-51	TL	58	24.00/5.0	3060	895	75.0	61500	35500	750	575
36.00-51	TL	58	26.00/5.0	3235	990	82.0	71000	41250	675	525
40.00-57	TL	68	29.00/6.0	3595	1095	82.0	92500	54500	725	550

OTR&ID

YB812



- Extra deep pattern, wide traction tread makes better delivery and operation performance
- Strength overstriking nylon cord provide outstanding loading capacity, thickening belt design improves puncture resistance
- Excellent cutting and tearing resistance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
36/65-33	TL	32	28.00/3.5	2030	890	106.0	22000			450
45/65-45	TL	58	36.00/4.5	2735	1140	125.0	50000			675

YB836



- Strength carcass structure, low heat build-up and tearing-resistance products formulation
- Wide tread, superior flotation, high passing performance
- Rib pattern provides good direction performance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							15km/h	50km/h	15km/h	50km/h
21.00-25	TL	16	15.00/3.0	1750	570	14.0	15000	8000	500	325
29.5-25	TL	28	25.00/3.5	1875	750	21.0	10625	9875	240	240

YB786



- Special rubber formulation design offers optimum cut resistance, puncture resistance and wear resistance, smooth thicker tread designed improves its puncture resistance against rock

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	Max. Load(kg)		Max.Pressure(kPa)	
						10km/h	15km/h	10km/h	15km/h
10.00-20	TT	16	7.5	1055	272	5080	4250	800	800

YB806



- Special rubber formulation design offers optimum cut resistance, puncture resistance and wear resistance, smooth thicker tread designed improves its puncture resistance against rock

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
12.00-24	TT	24	8.5	1245	315	34.0	7600	3750	975	550
14.00-24	TT	24	10.0	1370	375	44.0	9500	5150	850	575

OTR&ID

YB826



- Superior cut, wear, puncture resistance against rock, coal conditions, special tread formulation provides strong resistance to cutting and abrading

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							10km/h	50km/h	10km/h	50km/h
17.5-25	TL	16	14.00/1.5	1378	445	64.0	7300	4250	475	300
18.00-25	TL	40	13.00/2.5	1675	500	76.0	17000	9750	950	700
14.00-24	TT	24	10.0	1370	375	63.5	9500	5150	850	575

YB666



- Cutting and abrasion resistance tread design for long life
- Good traction and high passing performance
- Improved dual and wear resistance makes tyre safer by adopting strengthened steel cord
- Advanced tread compound ensure low heat-generating and better heat dissipation

Size	Type	Tra Code	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
								10km/h	50km/h	10km/h	50km/h
24.00R35	TL	E4	★★	17.00/3.5	2175	653	-	30750	18500	825	700
27.00R49	TL	E4	★★	19.50/4.0	2702	737	72.0	45000	27250	825	700
33.00R51	TL	E4	★★	24.00/5.0	3061	894	76.0	65000	38750	825	700
36.00R51	TL	E4	★★	26.00/5.0	3233	988	86.0	80000	46250	825	700
40.00R57	TL	E4	★★	29.00/6.0	3594	1097	88.0	100000	60000	825	700

YB688



- Cutting and abrasion resistance tread design for long life
- Good traction and high passing performance
- Improved dual and wear resistance makes tyre safer by adopting strengthened steel cord
- Advanced tread compound ensure low heat-generating and better heat dissipation

Size	Type	Tra Code	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
								10km/h	50km/h	10km/h	50km/h
40.00R57	TL	E4	★★	29.00/6.0	3594	1097	88.0	100000	60000	825	700

YB912



- Adopting strength nylon carcass construction,heavy duty capacity,suitable for extra twisting moment and extra heavy duty performance.
- Block and extra deep tread design makes it a much longer life

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load(kg)		Max.Pressure(kPa)	
							Single	Dual	Single	Dual
6.00-9	TT	10	4.00E	540	160	15.0	1505	1275	860	860
6.50-10	TT	10	5.00F	590	175	16.0	1655	1400	790	790
7.00-9	TT	10	5.00S	590	190	16.0	1995	1685	860	860
7.00-12	TT	12	5.00S	676	190	13.0	2375	2005	860	860
8.25-12	TT	12	6.5	765	235	21.0	3060	2585	720	720
8.25-15	TT	14	6.5	840	235	23.0	3775	3185	830	830
28x9-15	TT	14	7.0	710	220	18.0	3050	2575	970	970

OTR & ID

YB666



- Special pattern design for powerful gripping, effective resistance to irregular wearing, lower rolling resistance
- Tough belt for excellent over loading performance

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load (kg)	Max.Pressure (kPa)
10-15	TT	10	9.00	723	265	9.0	1260	300

YB616



- Wide tread design for stable handling and longer tire life
- High ply carcass construction for higher loading capacity
- Special pattern design for great gripping power on wet and muddy road conditions

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load (kg)	Max.Pressure (kPa)
12.00-18	TT	10	9.00V	1086	286	15.0	1650	280
12.00-18	TT	14	9.00V	1086	286	15.0	2350	470

YB617



- Overstriking nylon cord thread,new-style design, makes more loading Intensification breaker design,improve the stiffness of the crown
- Dilated and deepen pattern,improves the delivers stability, provides resistance to cutting & tearing

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load (kg)	Max.Pressure (kPa)
6.00-12	TT	8	4.50E	640	165	19.0	475	320
6.00-14	TT	6	4.50E	690	165	15.0	450	250
7.50-16	TT	6	5.50F	810	205	23.0	650	210
7.50-20	TT	6	5.50F	910	205	23.0	760	210
8.3-20	TT	6	W7	895	210	23.0	695	240
8.3-24	TT	6	W7	995	210	21.0	810	240
9.5-20	TT	8	W8	950	240	24.0	955	280
9.5-24	TT	10	W8	1050	240	25.0	1260	350
11.2-24	TT	10	W10	1105	285	29.0	1380	300
11.2-28	TT	8	W10	1205	285	29.0	1305	240
12.4-28	TT	8	W11	1260	315	30.0	1510	230
12.4-28	TT	10	W11	1260	315	30.0	1740	280
14.9-28	TT	10	W13	1365	378	38.0	2180	230
14.9-30	TT	10	W13	1415	378	39.0	2190	230
15-24	TT	10	DW14	1330	410	39.0	2800	280
15-24	TT	12	DW14	1330	410	39.0	3140	330
18.4-30	TT	14	W16L	1550	467	33.0	3400	260
10.5/75-15.3	TT	10	9.00	790	265	29.0	1525	390

AG

YB618

MEMO



- Stripe pattern,excellent steering.
- Optimum delivers stability

Size	Type	PR	Rim (mm)	O.D (mm)	S.W (mm)	NSD (mm)	Max. Load (kg)	Max.Pressure (kPa)
4.00-12	TT	8	3.00D	535	110	8.0	400	400
4.00-14	TT	4	3.00D	590	110	9.5	270	340
5.00-15	TT	6	4J	665	140	11.0	465	420
5.00-16	TT	6	4.00D	680	140	9.0	500	450
5.50-16	TT	6	4.00E	710	150	9.0	525	370
6.00-16	TT	8	4.00E	740	160	11.0	675	450
6.50-20	TT	8	5.00F	860	180	14.0	865	420
7.50-16	TT	8	5.50F	810	205	13.0	870	370



Series of horizontal dashed lines for taking notes.